

# Effective protection against lime formation: SYR's LEXsmart water softeners.



WiFi-enabled (optional)



## Single water softening systems LEXsmart

- Touch-display with easy menu navigation
- Compact control unit
- Analysis and statistics feature
- Adjustment of the regeneration intervals to consumption habits
- WiFi-enabled with the optional USB-stick, then controllable via the SYR App
- Connection equipment included

Compact control unit

Analysis and statistics feature



### Technical specifications

Operating pressure	Min. 2 bar, max. 8 bar			
Operating temperature	Min. 5 °C, max. 30 °C			
Ambient temperature	Min. 5 °C, max. 40 °C			
Fluid	Drinking water			
Power supply	6 W / 230V / 50 Hz			
	5 liters	12 liters	20 liters	30 liters
Flow rate at $\Delta p$ 1.0 bar	2.1 m³/h	2.1 m³/h	2.1 m³/h	2.1 m³/h
Capacity exchanger resin (in m³)	10 x °dH	24 x °dH	40 x °dH	60 x °dH

Short-term flow rate with which the ion exchanger can be operated. Very hard water can reduce the indicated nominal flow rate.

Serial number	LEXsmart 5 l	1500.03.005
	LEXsmart 12 l	1500.03.012
	LEXsmart 20 l	1500.03.020
	LEXsmart 30 l	1500.03.030



Innovative solutions for smart people